



STANDARD ASME CONVENTIONAL-TYPE HORIZONTAL PRESSURE TANKS
STANDARD ASME CODED HYDRO TANKS

DESIGNED FOR A WORKING PRESSURE OF 75 PSI.

INCLUDES EPOXY COATING ON INTERIOR & SHOP PRIME ON EXTERIOR.
 FOUR TO ONE SAFETY FACTOR BUILT INTO TANK AS PER TNRCC REGULATION.

1000 AND 1500 GALLON TANKS INCLUDE 11" X 15" ELIPTICAL MANWAYS
 EACH DOME (END).

ALL OTHER TANKS INCLUDE ONE 11" X 15" ELIPTICAL MANWAY IN ONE
 DOME AND ONE 14" X 18" ELIPTICAL MANWAY IN THE OPPOSITE DOME.

SPECIAL NOTE: DOES NOT CONTAIN 1/8" CORROSION ALLOWANCE.

THESE TANKS SATISFY AND PASS ALL CURRENT LAWS AND REGULATIONS
 BY THE TNRCC FOR PUBLIC USE WELLS AS WE ARE AWARE OF AT THE PRESENT.
 PRICES BELOW ARE ONLY APPROXIMATE. FINAL PRICES ARE ONLY GIVEN
 AFTER A SKETCH DRAWING IS PRESENTED FOR OUR ENGINEER TO EVALUATE
 FOR ANY COST ADJUSTMENTS.

<u>TANK SIZE</u>	<u>APPROXIMATE DIMENSIONS</u>
1000 GALLON-----	4'DIA. X 10' SEAM TO SEAM-----
1500 GALLON-----	4' " X 15' " " "-----
2000 GALLON-----	6' " X 8' " " "-----
2500 GALLON-----	6' " X 10' " " "-----
3000 GALLON-----	6' " X 12' " " "-----
4000 GALLON-----	6' " X 18' " " "-----
5000 GALLON-----	6' " X 22' " " "-----
6000 GALLON-----	8' " X 16' " " "-----
8000 GALLON-----	8' " X 20' " " "-----

COMES WITH ONE PAIR OF DETACHED SADDLES.

F.O.B. OUR YARD IN HOUSTON, TEXAS
 DELIVERY----NORMALLY 6 TO 8 WEEKS

DEPOSIT OF ONE-HALF OF THE COST OF THE TANK IS REQUIRED WHEN
 THE TANK IS ORDERED. BALANCE DUE UPON DELIVERY OF TANK.